"LED HANGING-LITE" EXIT SIGN SERIES

Features

- Attractive appearance
- Ceiling-mount
- Single-face or double-face application
- Minimum maintenance
- Lower power consumption
- c/w Clear acrylic panel
- Option: Flashing upon actuation by fire signal (dry contact)



"CRYSTALITE" Cat. CX-LED-405-P-HL

Legend











"CRYSTALITE" Cat. CX-LED-570-P-HL



Technical Data

Model	CX-LED-405-P-HL	CX-LED-570-P-HL
	GMS with white powder coating	
Lamp	Super Bright LED Line	
Line Voltage	A/C 220V~240V 50Hz +6%-10%	
Discharge Duration	3 Hours	
Recharge Period	12 Hours	
Battery	Sealed Ni-cd/ Ni-mh High Temperature Rechargeable Battery 14.4V 800mAh	
Power Consumption	~3W	
Operating Temp	0°C - 50°C	
Compliance	BS EN 60598-2-22; BS 5266-1; FSD PPA 104A(4 th Revision); FSD Code of Practice Clause 5.10 Exit Sign	

"LED HANGING-LITE SUPREME" EXIT SIGN SERIES

Features

- Attractive appearance and premier
- Ceiling mount with stainless steel metal case
- Hairline finishing, mirror finishing or golden plating finishing
- Single-face or double-face application
- Minimum maintenance
- Lower power consumption
- c/w Clear acrylic panel
- Option: Flashing upon actuation by fire signal (dry contact)



"CRYSTALITE" Cat. CX-LED-405-P-HL-G

Golden plating finishing

Legend



Directional Sign








"CRYSTALITE" Cat. CX-LED-570-P-HL-G

Golden plating finishing



Technical Data

Model	CX-LED-405-P-HL-H Hairline s/s finishing CX-LED-405-P-HL-M	CX-LED-570-P-HL-H Hairline s/s finishing CX-LED-570-P-HL-M
	Mirror s/s finishing	Mirror s/s finishing
	CX-LED-405-P-HL-G Golden plating finishing	CX-LED-570-P-HL-G Golden plating finishing
Lamp	Super Bright LED Line	
Line Voltage	A/C 220V~240V 50Hz +6%-10%	
Discharge Duration	3 Hours	
Recharge Period	12 Hours	
Battery	Sealed Ni-cd/ Ni-mh High Temperature Rechargeable Battery 14.4V 800mAh	
Power Consumption	~3W	
Operating Temp	0°C - 50°C	
Compliance	BS EN 60598-2-22; BS 5266-1; FSD PPA 104A(4 th Revision); FSD Code of Practice Clause 5.10 Exit Sign	